

Universe	Professional
Type	Verticality
Category	Harnesses
Subcategory	Harnesses for fall arrest, work positioning and suspension



AVAO® FAST International Version

The AVAO FAST harness is specifically designed for workers at height. Its design is specific to work positioning and rope descent. Contoured foam on the semi-rigid waistbelt and leg loops provide comfort during use. The waistbelt features metal side attachment points, equipment loops, and tool holder slots, allowing the user to organize all the necessary equipment for a day of work. Adjustment is quick, easy, and convenient, with self-locking DOUBLEBACK buckles and FAST opening buckles.



With an ergonomic construction, the AVAO FAST harness allows users to work and move comfortably throughout the workday.



Textile loop on the ventral connection point (for installing a lanyard with a RING OPEN) and a metal D ring (for installing a PODIUM or LITEPOD work seat).



The waistbelt is equipped with five equipment loops and two slots for tool holders, for optimal equipment management.



Leg loops are equipped with FAST opening buckles that fasten and unfasten quickly and easily, even while wearing gloves, without needing to readjust.

Short Description Comfortable and versatile harness for work at height

Selling Points

- Comfortable construction:
 - Widely spaced shoulder straps reduce neck chafing
 - Sliding straps provide more freedom and ease of movement
 - All contact zones use contoured foam and are lined with breathable material, including the shoulder straps, waistbelt and leg loops, making it more comfortable to work and move around
 - Semi-rigid waistbelt and leg loops provide optimal harness fit and support
 - Metal side attachment points can be folded down to prevent them snagging accidentally when not in use
 - Elastic leg loop bands (replaceable and available as an accessory) allow the harness to maintain the right adjustment whether the user is walking or suspended
- Convenient and quick to adjust:
 - Self-locking DOUBLEBACK buckles on the shoulder straps and waistbelt, and FAST opening buckles on the leg loops make adjustments quick, easy, and convenient
 - Anti-slip devices installed on the DOUBLEBACK buckles help maintain the right adjustment throughout the workday
- Easy to carry and organize equipment:
 - Shoulder straps are equipped with a parking system for fall-arrest lanyard connectors, keeping the lanyard out of the user's way and the connectors within reach
 - Metal ventral D ring is equipped with connection points to install a PODIUM or LITEPOD work seat
 - Ventral connection point features a textile loop that allows the user to install a lanyard with a RING OPEN attachment ring
 - Two side metal attachment points for connecting a positioning lanyard in double mode
 - Five pre-shaped equipment loops with protective sheath
 - Two slots for CARITOOL tool holders or the INTERFAST connection system
- In the event of a fall on the dorsal attachment point, a red indicator appears, signaling that the harness should be retired

Specification

- Ventral attachment point: Attachment for a descender, a positioning lanyard in single mode, a work seat on the ventral D ring; attachment for a lanyard with a RING OPEN to the textile connection point
- Lateral attachment points: Attachment for a positioning lanyard for use in double mode
- Sternal attachment point: Attachment for a fall-arrest system
- Dorsal attachment point: Attachment for a fall-arrest system
- Rear attachment point on the waistbelt: Attachment for a restraint lanyard
- Certification(s): CE EN 361, CE EN 813, CE EN 358, ANSI Z359.11, ANSI Z459.1, CSA Z259.10, NFPA 1983 class 3, GB 6095: Q-W-Z, compliant with the Japanese standard for fall protection
- Material(s): Nylon, polyester, aluminum, steel

Specifications by reference

Reference(s)	C071DB00	C071DB01	C071DB02	C071DB03
Color(s)	Black, Yellow	Black, Yellow	Black, Yellow	Black
Size	0	1	2	0
Waist belt	65-80 cm	70-93 cm	83-120 cm	65-80 cm
Leg loops	44-59 cm	47-62 cm	50-65 cm	44-59 cm
Stature	160-180 cm	165-185 cm	175-200 cm	160-180 cm
Weight	2060 g	2100 g	2200 g	2060 g
Made in	RO	RO	RO	RO
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	3	3	3	3
EAN	3342540845473	3342540845497	3342540845503	3342540845510

Reference(s)	C071DB04	C071DB05
Color(s)	Black	Black
Size	1	2
Waist belt	70-93 cm	83-120 cm
Leg loops	47-62 cm	50-65 cm
Stature	165-185 cm	175-200 cm
Weight	2100 g	2200 g
Made in	RO	RO
Guarantee	3 years	3 years
Inner Pack Count	1	1
Quantity Per Box	3	3
EAN	3342540845527	3342540845534

Spare part(s) Elastic Keepers 45 mm
Plastic Keepers 45 mm

Accessory(ies) RING OPEN
CARITool
INTERFAST
TOOLEASH
MINO
Shackles

Related product(s) ASAP®
ASAP® LOCK
ASAP'SORBER
PODIUM
LITEPOD
I'D® L
ABSORBICA®-Y MGO International Version
PROGRESS ADJUST-I Progression Lanyard
JANE-I
PROGRESS ADJUST-Y
GRILLON
